

**ACOUSTICS2008/1670**  
**Laser ultrasonic study of Lamb wave propagation in different film loading configurations**

Xiaodong Xu<sup>a</sup>, G. Shkerdin<sup>b</sup> and Christ Glorieux<sup>c</sup>

<sup>a</sup>Modern Acoustics, Institute of Acoustics, Nanjing University, 210093 Nanjing, China

<sup>b</sup>Laboratorium voor Akoestiek en Thermische Fysica - Departement Natuurkunde en Sterrenkunde -  
Katholieke Universiteit Leuven, Celestijnenlaan 200D, B-3001 Leuven, Belgium

<sup>c</sup>Lab. ATF, Katholieke Universiteit Leuven, Celestijnenlaan 200D, B-3001 Leuven, Belgium

A study is performed concerning the propagation Lamb waves in technologically and scientifically interesting configurations. In a first configuration a thin film was loaded with different liquids on its two sides. Three experimental laser ultrasonic configurations, line excitation with scanning detection, grating excitation with single point detection, and grating excitation with scanning probe beam, were implemented. All experimental results were found to be consistent between experimental methods and with theoretical predictions. The configuration can be implemented in monitoring applications where elastic properties of liquids that are kept in containers can be determined via the outside container wall. In a second configuration laser excited and detected Lamb waves in a rubber-metal bi-layer were used to determine the highly damped elastic properties of rubber.